

PROMETAL INTERNATIONAL CO., LTD.

MILL INSPECTION CERTIFICATE

CONTRACT NUMBER : PRO-S-171225B-VOS
 CUSTOMER: KONINENTAL LTD
 COMMODITY: PRIME COLD ROLLED STAINLESS STEEL SHEET, SLIT EDGE, 430 2B FINISH WITH PE
 PRIME COLD ROLLED STAINLESS STEEL SHEET, SLIT EDGE, 430 BA FINISH WITH PE
 PRIME COLD ROLLED STAINLESS STEEL SHEET, SLIT EDGE, 430 N4 FINISH WITH PE

DATE: 2018/3/16
 SPECIFICATION: ASTM A240/A480M
 MILL NAME & ADDRESS: ANGAN HAN YANG STAINLESS STEEL CORP.
 NO.2 HANGUANG STREET EAST SECTION, GUANGZHOU
 DEVELOPMENT DISTRICT, GUANGZHOU, CHINA

| NO. | SIZE(MM) | GRADE/ FINISH | COIL NO. | N.W. (KGS) | CHEMICAL COMPOSITION(%) | | | | | | | | | | | HARDNESS | | TENSILE TEST | | | |
|--------|-------------------------|------------------|----------------|---------------|-------------------------|-------|------|-------|-------|------|-------|----|----|---|-----|----------|-----------|--------------|--------|----|--|
| | | | | | C | Si | Mn | P | S | Ni | Cr | Mo | Cu | N | HRB | HV | 0.2% Y.S. | T.S. | EL (%) | | |
| 1 | 0.5MM X 1000MM X 2000MM | 430/2B | F30R1801-187-1 | 1,750 | 0.044 | 0.320 | 0.41 | 0.020 | 0.001 | 0.10 | 16.22 | | | | | | 159 | 301 | 505 | 24 | |
| 2 | 0.5MM X 1000MM X 2000MM | 430/2B | F30R1801-187-1 | 1,600 | 0.044 | 0.320 | 0.41 | 0.020 | 0.001 | 0.10 | 16.22 | | | | | | 159 | 301 | 505 | 24 | |
| 3 | 0.5MM X 1000MM X 2000MM | 430/2B | F30R1801-193-2 | 2,040 | 0.044 | 0.320 | 0.41 | 0.020 | 0.001 | 0.10 | 16.22 | | | | | | 159 | 301 | 505 | 24 | |
| 4 | 0.5MM X 1250MM X 2500MM | 430/2B | F30R1712-308-C | 1,920 | 0.034 | 0.380 | 0.45 | 0.023 | 0.001 | 0.11 | 16.15 | | | | | | 154 | 302 | 501 | 28 | |
| 5 | 0.5MM X 1000MM X 2000MM | 430/BA | F30R1801-193-2 | 1,662 | 0.044 | 0.320 | 0.41 | 0.020 | 0.001 | 0.10 | 16.22 | | | | | | 159 | 301 | 505 | 24 | |
| 6 | 0.5MM X 1000MM X 2000MM | 430/BA | F30R1801-193-2 | 1,662 | 0.044 | 0.320 | 0.41 | 0.020 | 0.001 | 0.10 | 16.22 | | | | | | 159 | 301 | 505 | 24 | |
| 7 | 0.5MM X 1000MM X 2000MM | 430/BA | F30R1801-193-2 | 1,658 | 0.044 | 0.320 | 0.41 | 0.020 | 0.001 | 0.10 | 16.22 | | | | | | 159 | 301 | 505 | 24 | |
| 8 | 0.5MM X 1000MM X 2000MM | 430/BA | F30R1801-193-2 | 1,586 | 0.044 | 0.320 | 0.41 | 0.020 | 0.001 | 0.10 | 16.22 | | | | | | 159 | 301 | 505 | 24 | |
| 9 | 0.5MM X 1250MM X 2500MM | 430/BA | L30R1712-178-C | 1,848 | 0.037 | 0.290 | 0.36 | 0.020 | 0.001 | 0.13 | 16.10 | | | | | | 152 | 299 | 492 | 29 | |
| 10 | 0.5MM X 1250MM X 2500MM | 430/BA | L30R1712-178-C | 1,850 | 0.037 | 0.290 | 0.36 | 0.020 | 0.001 | 0.13 | 16.10 | | | | | | 152 | 299 | 492 | 29 | |
| 11 | 0.5MM X 1250MM X 2500MM | 430/BA | L30R1712-178-C | 1,836 | 0.037 | 0.290 | 0.36 | 0.020 | 0.001 | 0.13 | 16.10 | | | | | | 152 | 299 | 492 | 29 | |
| 12 | 0.5MM X 1250MM X 2500MM | 430/BA | L30R1712-178-C | 1,838 | 0.037 | 0.290 | 0.36 | 0.020 | 0.001 | 0.13 | 16.10 | | | | | | 152 | 299 | 492 | 29 | |
| 13 | 0.8MM X 1250MM X 2500MM | 430/BA | L30R1712-164-D | 2,128 | 0.033 | 0.330 | 0.39 | 0.022 | 0.001 | 0.10 | 16.24 | | | | | | 152 | 305 | 502 | 29 | |
| 14 | 0.5MM X 1250MM X 2500MM | 430/2B | F30R1712-308-C | 1,926 | 0.034 | 0.380 | 0.45 | 0.023 | 0.001 | 0.11 | 16.15 | | | | | | 154 | 302 | 501 | 28 | |
| 15 | 0.5MM X 1250MM X 2500MM | 430/2B | F30R1712-308-C | 1,914 | 0.034 | 0.380 | 0.45 | 0.023 | 0.001 | 0.11 | 16.15 | | | | | | 154 | 302 | 501 | 28 | |
| 16 | 0.8MM X 1250MM X 2500MM | 430/2B | F30R1712-325-C | 1,638 | 0.028 | 0.380 | 0.37 | 0.024 | 0.001 | 0.15 | 16.15 | | | | | | 155 | 305 | 494 | 29 | |
| 17 | 0.8MM X 1250MM X 2500MM | 430/2B | F30R1712-325-C | 1,638 | 0.028 | 0.380 | 0.37 | 0.024 | 0.001 | 0.15 | 16.15 | | | | | | 155 | 305 | 494 | 29 | |
| 18 | 0.8MM X 1250MM X 2500MM | 430/2B | F30R1712-325-C | 1,642 | 0.028 | 0.380 | 0.37 | 0.024 | 0.001 | 0.15 | 16.15 | | | | | | 155 | 305 | 494 | 29 | |
| 19 | 0.8MM X 1250MM X 2500MM | 430/2B | F30R1712-325-C | 1,648 | 0.028 | 0.380 | 0.37 | 0.024 | 0.001 | 0.15 | 16.15 | | | | | | 155 | 305 | 494 | 29 | |
| 20 | 0.8MM X 1250MM X 2500MM | 430/2B | F30R1712-325-C | 1,586 | 0.028 | 0.380 | 0.37 | 0.024 | 0.001 | 0.15 | 16.15 | | | | | | 155 | 305 | 494 | 29 | |
| 21 | 0.5MM X 1250MM X 2500MM | 430/N4 | L30R1712-178-D | 1,946 | 0.037 | 0.290 | 0.36 | 0.020 | 0.001 | 0.13 | 16.10 | | | | | | 152 | 299 | 492 | 29 | |
| 22 | 0.5MM X 1250MM X 2500MM | 430/N4 | L30R1712-178-D | 1,896 | 0.037 | 0.290 | 0.36 | 0.020 | 0.001 | 0.13 | 16.10 | | | | | | 152 | 299 | 492 | 29 | |
| 23 | 0.8MM X 1250MM X 2500MM | 430/N4 | F30R1712-325-D | 2,136 | 0.028 | 0.380 | 0.37 | 0.024 | 0.001 | 0.15 | 16.15 | | | | | | 155 | 305 | 494 | 29 | |
| 24 | 1.0MM X 1250MM X 2500MM | 430/N4 | F30R1712-305-C | 1,974 | 0.034 | 0.380 | 0.45 | 0.023 | 0.001 | 0.11 | 16.15 | | | | | | 154 | 306 | 485 | 29 | |
| 25 | 1.0MM X 1250MM X 2500MM | 430/N4 | F30R1712-305-C | 1,974 | 0.034 | 0.380 | 0.45 | 0.023 | 0.001 | 0.11 | 16.15 | | | | | | 154 | 306 | 485 | 29 | |
| 26 | 1.0MM X 1250MM X 2500MM | 430/N4 | F30R1712-305-C | 1,930 | 0.034 | 0.380 | 0.45 | 0.023 | 0.001 | 0.11 | 16.15 | | | | | | 154 | 306 | 485 | 29 | |
| TOTAL: | | | | 47,226 | | | | | | | | | | | | | | | | | |

REMARK:

WE HEREBY CERTIFY THAT MILL TEST CERTIFICATE INCLUDING ACTUAL MECHANICAL PROPERTIES AND ACTUAL CHEMICAL COMPOSITION.


 AUTHORIZED SIGNATURE
 For and on behalf of
PROMETAL INTERNATIONAL CO., LTD.
 Authorized Signature

74046